

PATENT

Att. Dkt. No. WEAT/0487

IN THE CLAIMS:

1. (Currently Amended) An expander tool for use in a wellbore, the expander tool comprising:

a body having at least one recess formed therein; and

an expansion assembly disposable in the at least one recess, the expansion assembly comprising:

a piston that is ~~outwardly~~ radially extendable from the body in response to ~~the radially outward~~ a fluid force; ~~[[and]]~~

a roller rotationally disposed on a shaft, wherein the roller and the shaft are constructed and arranged on the piston at an angle relative to a longitudinal axis of the expander tool; and

a bearing member disposed adjacent an end of the roller, wherein the bearing member is matable to the roller thereby preventing relative rotation therebetween.

2. (Original) The expander tool of claim 1, wherein the angle is outward from a center line of the expander tool.

3. (Currently Amended) The expander tool of claim 1, wherein the bearing member includes a bearing profile matable with a corresponding profile formed in the roller ~~further including a bearing body disposed adjacent the roller.~~

4. (Cancelled)

5. (Currently Amended) The expander tool of claim 1 ~~[[4]]~~, further including a second wherein the bearing body member disposed adjacent the bearing member, wherein the second bearing member is further includes a back bearing body ~~operatively attached to the piston, thereby remaining rotationally stationary.~~

PATENT

Atty. Dkt. No. WEAT/0487

6. (Currently Amended) The expander tool of claim 5, further including a cooling channel disposed between the bearing members ~~front bearing body and the back bearing body~~.
7. (Currently Amended) The expander tool of claim 6, wherein the cooling channel is a helical groove formed in the bearing member ~~front bearing body~~.
8. (Original) The expander tool of claim 7, wherein the cooling channel is a fluid path constructed and arranged to promote the ingress of a fluid therein.
9. (Currently Amended) The expander tool of claim 8, wherein the fluid creates a fluid cushion between the bearing members ~~front bearing body and the back bearing body~~, thereby reducing the friction therebetween.
10. (Original) The expander tool of claim 2, wherein the shaft is angled at 10.0 degrees relative to the longitudinal axis of the expander tool.
11. (Original) The expander tool of claim 10, wherein the roller is tapered to provide an outer surface thereof at 20.0 degrees from the longitudinal axis of the expander tool.
12. (Original) The expander tool of claim 1, further including a second roller disposed adjacent the roller, the second roller having a smaller outer diameter than the roller.
13. (Original) The expander tool of claim 12, wherein the second roller rotates at a different rate than the roller.
14. (Original) The expander tool of claim 1, wherein an outer diameter portion of the piston includes at least a portion disposed at either end thereof having an outer

PATENT

Atty. Dkt. No. WEAT/0487

surface for substantially contacting an inner surface of the recess, the portions having substantial width to prevent tipping of the piston in the recess.

15. (Currently Amended) An expander tool for use in a wellbore, the expander tool comprising:

a body having at least one recess formed therein; and

an expansion assembly disposable in the at least one recess, the expansion assembly comprising:

a piston which is outwardly extendable from the body in response to the radially outward force;

a roller rotationally disposed on a shaft;

an upper bearing body disposed on the shaft adjacent an upper end of the roller, ~~wherein the upper bearing body includes a front bearing body and a rear bearing body;~~ and

a lower bearing body disposed on the shaft adjacent a lower end of the roller.

16. (Currently Amended) The expander tool of claim 15, wherein the upper bearing body includes a front bearing body ~~is operatively attached to~~ matable with the roller, thereby rotating with the roller.

17. (Currently Amended) The expander tool of claim 16 ~~[[15]]~~, wherein the upper bearing body includes a back bearing body ~~is operatively attached to~~ matable with the piston, thereby remaining rotationally stationary.

18. (Currently Amended) The expander tool of claim 17 ~~[[15]]~~, further including a cooling channel disposed between the front bearing body and the back bearing body.

19. (Original) The expander tool of claim 15, wherein an outer diameter portion of the piston includes at least a portion disposed at either end thereof having an outer

PATENT

Atty. Dkt. No. WEAT/0487

surface for substantially contacting an inner surface of the recess, the portions having substantial width to prevent tipping of the piston in the recess.

20. (Currently Amended) An expander tool for use in a wellbore, the expander tool comprising:

a body having at least one recess formed therein; and

an expansion assembly disposable in the at least one recess, the expansion assembly comprising:

a piston disposable within a recess of the expander tool, the piston being outwardly extendable from a body of the expander tool in response to a radially outward force;

a first roller rotationally disposed on a shaft; [[and]]

a second roller rotationally disposed on the shaft adjacent the first roller, whereby the second roller rotates at a different rate than the first roller; and

at least one bearing member disposed between the first roller and the second roller.

21. (Original) The expander tool of claim 20, wherein the expansion assembly comprises at least one additional roller.

22. (Original) The expander tool of claim 20, wherein the first and second rollers and the shaft are constructed and arranged on the piston at an outward angle relative to a longitudinal axis of the expander tool.

23. (Original) The expander tool of claim 20, wherein the first and second rollers are angled at 10.0 degrees relative to the longitudinal axis of the expander tool.

24. (Original) The expander tool of claim 20, further including a bearing body disposed adjacent the first roller, the bearing body having a front bearing body and a back bearing body.

PATENT

Att. Dkt. No. WEAT/0487

25. (Original) The expander tool of claim 24, further including a cooling channel disposed between the front bearing body and the back bearing body.

26. (Original) The expander tool of claim 25, wherein the cooling channel is a helical groove formed in the front bearing body.

27. (Original) The expander tool of claim 25, wherein the cooling channel is a fluid path constructed and arranged to promote the ingress of a fluid therein.

28. (Original) The expander tool of claim 27, wherein the fluid creates a fluid cushion between the front bearing body and the back bearing body, thereby reducing the friction therebetween.

29. (Currently Amended) A method for expanding a tubular body within a wellbore, comprising:

disposing an expander tool at a lower end of a working string, the expander tool having a body and a plurality of recesses formed therein for receiving an expansion assembly, each expansion assembly comprising:

a piston which is outwardly extendable from the body in response to a radially outward force;

a roller rotationally disposed on a shaft;

an upper bearing body disposed on the shaft adjacent an upper end of the roller, ~~wherein the upper bearing body includes a front bearing body and a rear bearing body;~~ and

a lower bearing body disposed on the shaft adjacent a lower end of the roller;

placing the expander tool into the wellbore proximate the tubular body;
activating the expander tool, wherein the expansion assembly extends radially outward; and

expanding the tubular body within the wellbore.

PATENT

Atty. Dkt. No. WEAT/0487

30. (Currently Amended) The method of claim 29, wherein the upper bearing body includes a front bearing body is operatively attached to matable with the roller, thereby rotating with the roller and the back bearing body ~~is operatively attached to matable with~~ the piston, thereby remaining rotationally stationary.

31. (Original) The method of claim 30, wherein a cooling channel is disposed between the front bearing body and the back bearing body.

32. (Original) The method of claim 31, further including providing a fluid into the cooling channel to cool the bearing body and reduce the friction between the front bearing body and the back bearing body.

33. (Currently Amended) An expansion assembly for use with an expander tool; the expansion assembly comprising:

a piston disposable within a recess of the expander tool, the piston being outwardly extendable from a body of the expander tool in response to a radially outward force;

a roller rotationally disposed on a shaft, wherein the roller and the shaft are constructed and arranged on the piston at an angle relative to a longitudinal axis of the expander tool; and

a bearing body disposed adjacent the roller, wherein the bearing body includes a profile matable with a corresponding profile formed on the roller.

34. (Original) The expansion assembly of claim 33, wherein the bearing body includes a front bearing body operatively attached to the roller, thereby rotating with the roller.

35. (Original) The expansion assembly of claim 34, wherein the bearing body further includes a back bearing body operatively attached to the piston, thereby remaining rotationally stationary.

Page 7

362032_1

PATENT

Atty. Dkt. No. WEAT/0487

36 (Original) The expansion assembly of claim 35, further including a cooling channel disposed between the front bearing body and the back bearing body.

37. – 38. (Cancelled)

Please add the following new claims:

39. (New) An expander tool for use in a wellbore, the expander tool comprising:
a body having a bore therethrough;
at least one recess formed on an outer surface of the body;
at least one slidable member disposed in the at least one recess, wherein the slidable member includes at least a portion disposed at either end thereof having an outer surface for substantially contacting an inner surface of the recess, the portions having sufficient width to substantially prevent tilting about an axis perpendicular to a longitudinal axis of the tool; and
a rotating member mounted on the slidable member.
40. (New) The expander tool of claim 39, wherein the slidable member is radially extendable from the body in response to a fluid force.
- 41 (New) The expander tool of claim 15, wherein the roller and the shaft are constructed and arranged on the piston at an angle relative to a longitudinal axis of the expander tool.